




CALTEX

特级抗磨液压油 (Rando® HD) 优质抗磨液压传动油



特点

液压油使用寿命更长

||

保护设备

减少故障停机

||

无故障安全运行

适用范围

-
-
-
-
-
-
-
-

产品概要

||

A Chevron company brand



Our Family of Brands

重要特性参数

特级抗磨液压油 Rando® HD						
ISO	22	32	46	68	100	150
	520209	520210	520211	520212	520213	520214
@50 ,	1.1	1.1	2.0	3.5	12	15
	190	216	238	240	240	250
FZG	12	12	12	12	12	11
	-42	-39	-36	-36	-30	-30
(TOST)		5000+	4500+	4500+		
mm ² /s@40	21.0	30.5	44.0	65.0	92.0	145
mm ² /s@100	4.3	5.4	6.8	8.9	11.4	15.0
	110	110	110	110	110	105

1201PRC

性能标准

Rando HD

- Parker Hannifin (Denison Hydraulics) HF-0 (ISO 32, 46, 68)
- Eaton Vickers I-286-S (), M-2950-S ()(ISO 32, 46, 68)
- David Brown 0A(ISO 32), 1A(ISO 46), 2A(ISO 68), 3A(ISO 100), 4A(ISO 150)

Rando HD

Cincinnati Machine P-68 (ISO 32) P-69 (ISO 68) P-70 (ISO 46)

Rando HD

- Bosch Rexroth RE 07 075
- ISO 6743:1999 4 HM
- ISO 11158:2009, HM
- DIN 51502:1990, HLP
- DIN 51524:2006-04 2 , HLP (ISO 22, 32, 46, 68, 100)

环境、健康与安全

(MSDS)

Chevron Lubricants
- Asia Pacific